

DECLARATION OF PERFORMANCE

No 2/F/IZOL/2018/EN

1. Unique identification code of the product type:

IZOROL – PP EPS T 040

2. Intended use/es:

Product IZOROL – PP EPS T 040 is used in thermal insulation in construction

3. The manufacturer:

Kotar Sp. z o.o.
ul. Kościuszki 33, 56-100 Wołów
Tel.: +48 71 389 23 16 Fax: +48 71 389 44 94 Email: kotar@kotar.pl

4. System or systems of assessment and verification of constancy of performance of the construction:

System 3

5. Harmonised standard:

EN 13163:2012+A1:2015 „Thermal insulation products for buildings- Factory made expanded polystyrene (EPS) products- Specification.”

6. Notified body/ies:

- **MPA BAU HANNOVER, Jednostka notyfikowana numer – 0764**
- **Centralny Ośrodek Badawczo – Rozwojowy Przemysłu Izolacji Budowlanej, Jednostka notyfikowana numer - 1486**

7. Declared performance/s:

Table no.1

Essential characteristics	Clauses in this and European standard(s) related to Essentials characteristics	Regulatory classes/NPD ¹	Harmonised technical specification
Thermal resistance	Thermal resistance and Thermal conductivity	R_D – (Table no. 2) At most 0,040 W/m·K	EN 13163:2012 +A1:2015
	Thickness	$T(0)$ (± 0 mm) d_N (Table no. 2)	
Reaction to fire	Reaction to fire	E	
Durability of reaction to fire against heat, weathering, ageing /degradation	Durability characteristics	NPD	
Durability of thermal resistance against heat, weathering, ageing/degradation	Thermal resistance and Thermal conductivity	R_D – (Table no.2) At most 0,040 W/m·K	
	Durability characteristics	NPD	
Compressive strength	Compressive stress or Compressive strength	NPD	
Tensile/Flexural strength	Bending strength	BS50 (≥ 50 kPa)	
	Tensile strength perpendicular to faces	NPD	
Durability of reaction to fire against heat, weathering, ageing /degradation	Compressive creep	NPD	
	Freeze-thaw resistance	NPD	
	Long-term thickness reduction	NPD	
Water permability	Long term water absorption by immersion	NPD	
	Long term water absorption by diffusion	NPD	
Water vapour permeability	Water vapour transmission	NPD	

Kotar Sp. z o.o

ul. Kościuszki 33
56-100 Wołów
e-mail: kotar@kotar.pl
www.kotar.pl

tel. +48/71 389 23 16
+48/71 389 44 94
fax +48/71 389 44 94 wew. 21

Sąd Rejonowy dla Wrocławia-Fabrycznej,
IX Wydział Gospodarczy Krajowego
Rejestru Sądowego
KRS: 0000708604
Kapitał Zakładowy 1.100.000,00 zł

NIP: 917-000-27-93
NIPUEPL9170002793
Regon: 931615130
KONTO BZ WBK SA 1 o/Wołów:
62 1090 2460 0000 0006 2200 1593

Impact noise transmission index (for floors)	Dynamic stiffness	SD20 for thickness >30 mm SD25 for thickness = 30mm SD30 for thickness < 30mm
	Thickness	NPD
	Compressibility	CP2
Continuous glowing combustion	Continuous glowing combustion	NPD
Release of dangerous substances to the indoor environment	Release of dangerous substances	NPD

¹ NPD – No performance determined

Table no.2: Declared thermal resistance R_D [m^2K/W]:

Thickness [mm]	20	25	30	35	40
Declared Value [m^2K/W]	0,50	0,60	0,75	0,85	1,00

Website address where is available this declaration of performance:

<http://www.kotar.pl>

The performance of the product identified above is in conformity with a set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (UE) no 305/2011 under the sole responsibility of the manufacturer identified above.

Information provided with declaration of performance

- Information referred to in article 31 of ordinance (EC) no. 1907/2006 (REACH)
 - Not applicable
- Information about substances contained in the product specified in article 33 of ordinance (EC) no. 1907/2006 (REACH)
 - Not applicable


Name and signature of entitled person:

Marcin Jaworski

(name and surname)

Wołów, 02.01.2018 r.

(place and date)

KOTAR Sp. z o.o.

 Marcin Jaworski
 Prezes Zarządu
(signature)